

TECHNICAL DATA SHEET



Type no.		SHD 680 32	
Article no.		018680320101	
Standards		DIN EN 50342-1, 50342-4	
Application		Starter battery	
Electrical data			
Rated voltage		12V	
Rated capacity		180 Ah (K20)	
Cold start current		1000 A (EN)	
Dimensions and weights			
Box		B	
Length max.		514mm	
Width max.		223mm	
Box height max.		195mm	
Total height max.		220mm	
Battery weight		Ca. 46,0 kg (+/- 5 %)	
Electrolyte density		Approx. 1,28 kg/l	
Electrolyte		Diluted sulphuric acid	
Items/pallet		21	
Pallet ID		Euro pallet	
Items per layer		7	
Features			
Base hold-down		B00	
Layout		3	
Terminal		1	
Separator		PE bag separator with glass nonwoven	
Degassing		Battery with single degassing	
Flame arrester		Integrated	
Performance identification		W4 - C2 - V3 - E3	
Maintenance ¹⁾			
Water consumption		W4	
Refill water		Distilled or demineralised (DIN 43530)	
Self-discharge		Approx. 5 % per month	
Charging current		Approx. 1/10 of the rated capacity	
Charging voltage ²⁾		max. 14,4 V	



¹⁾ All the listed values relate to room temperature +25° C

²⁾ Recommendation with an external, voltage-regulated charge. Attention: Temperature compensation in case of deviation!

1 Document DBTBAT00339 prepared on 2018-04-01 ; Rights relating to changes and errors retained.
original