

LEDiving FX | Functional series



Product family features

- Different high beam patterns (spot or combo) available
- Powerful far field illumination
- Extremely high optic efficiency, homogeneous light distribution and reduced glaring
- Premium OSRAM quality
- Robust and compact design with long lifetime of up to 5,000 h thanks to integrated driver and thermal management system

Product datasheet

Technical data

Electrical data

Nominal voltage	12/24 V
Nominal wattage	35 W

Dimensions & weight

Length	655.0 mm
Product weight	2100.00 g

Country specific categorizations

Order reference	LEDDL104-SP 12/
-----------------	-----------------

Product datasheet

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4052899595378		Folding carton box 1	638 mm x 137 mm x 90 mm	7.87 dm ³	2338.00 g
4052899595385		Shipping carton box 4	655 mm x 295 mm x 208 mm	40.19 dm ³	10166.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Legal advice

Detailed guarantee terms can be found at www.osram.com/am-guarantee.
Driving lights must be installed in pairs for 12/24 V-vehicles.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.